

MORE TOOLS



SPECIFICATIONS

| Dimensions | 1.4 in. H x 2.4 in. W x 4.3 in. L (36 mm x 61 mm x 109 mm) |
|--------------------------|--|
| Weight | 2.3 oz. (65 g) without battery |
| Battery Type | 9-V alkaline (not included) |
| Low Battery Indicator | Unit will beep to indicate low battery |
| Battery Life | 72 hours of continuous alarm, up to two years idle depending on use |
| Sound Intensity | 85 dB at 10 ft. (3 m) |
| Operating Temperature | 32° to 120°F (0° to 49°C) |
| Storage Temperature | -20° to 150°F (-29° to 66°C) |
| Humidity | 80% (non-condensing) |
| Shock Resistance | Shock resistant from a 6 ft. (1.8 m) drop onto concrete |
| Water Resistance | Splash and water resistant, not waterproof. Floats on surface if battery is installed correctly. |

Leak Alert[™]

Electronic Water Detector

Prevent serious water damage in your home with the help of Leak Alert[™] water detector. This self-contained battery-powered unit will sound a loud alarm the second it gets wet, alerting you to a potential water leak.

Place it anywhere the potential for flooding or leaking exists:

- Under sinks
- Near water heaters
- In basements
- Near dishwashers and refrigerators
- Under fish tanks
- Near plumbing and toilets
- Loud alarm (85 dB) sounds for up to 72 hours
- In the event of a flood, unit will float and continue to sound alarm until battery is depleted
- Fully automatic operation—no wiring required
- Low battery indicator for optimum safety and performance



O 2010. Leak Alert and Zircon are trademarks or registered trademarks of Zircon Corporation • C/N 1873 09/10